





# **Features**

- · Space-saving 21" (533 mm) wide design.
- Produces up to 770 lbs (349 kg) of ice per day.
- · Soft, chewable nugget ice crystals.
- · Cools beverages faster and longer while maintaining flavors better.
- · Decreased water and power usage compared to cube ice makers.
- SystemSαfe load monitoring system constantly checks workload on gearbox, shutting down system before a problem develops and preventing costly repairs.
- · Water Sensor eliminates low or no water failures and cannot be affected by adverse water conditions.
- · Rugged stainless steel evaporator and auger ensures reliability.
- · Industrial-grade roller bearings and heavy-duty gearbox provide years of trouble-free service.

# **Options & Accessories**

WATER FILTERS							
Ice Machine	Manifold						
Model	System	Replacement					
GEM0650	IFQ1	IOMQ (1)					
GEM0655	IFQI	IOMQ (I)					

## Ice Maker Warranty

Every Ice-O-Matic ice maker is backed by a warranty that provides both parts and labor coverage.

- Three years Parts and Labor for all nugget ice maker parts.
- Five years **Parts** coverage on the compressor.

#### Ice Form



NUGGET ICE DIMENSIONS						
H x Dia. (in.)	1/2 x <b>3</b> /8					
H x Dia. (mm)	12.7 x 9.5					

## Bin Chart Kits for Combining Wider Bins with Smaller Models

	ICE STORAGE BINS										
	Model No. Capacity Width	<b>B25</b> 242 lbs (110 kg) 30 in (762 mm)	<b>B40</b> 344 lbs (156 kg) 30 in (762 mm)	<b>B42</b> 351 lbs (160 kg) 22in (559 mm)	<b>B55</b> 510 lbs (232 kg) 30 in (762 mm)	<b>B700</b> 680 lbs (308 kg) 30 in (762 mm)	<b>B110</b> 854 lbs (388 kg) 48 in (1,219 mm)	<b>B1000</b> 1000 lbs (454 kg) 48 in (1,219 mm)	<b>B1300</b> 1320 lbs (599 kg) 48 in (1,219 mm)	<b>B1325</b> 1325 lbs (601 kg) 60 in (1,524 mm)	<b>B1600</b> 1660 lbs (753 kg) 60 in (1,524 mm)
Kits	GEM0650/ GEM0655	KBT19		KBT24	KBT19	Kit Not Required	KBT23	Kit Not Required			
	GEM0650/ GEM0655 (2)			N/A			KBT222	Kit Not Required			

\*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers












# GEMO650/0655 - NUGGET ICE MAKER



#### Air Cooled


Please note: air-cooled units require 6" (152 mm) clearance for air intake and exhaust.


- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Electrical inlet.



## Water Cooled/Remote

- A. Ice maker water in, 3/8' FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Electrical inlet.
- D. Condenser water in, 3/8' (water cooled only).
- E. Condenser water out, 1/2" (water cooled only).
- F. Liquid line, 3/8' male coupling for precharged line set (remote only).
- G. Discharge line, 1/2" male coupling for precharged line set (remote only).
- H. Remote condenser junction box (remote only).





# **Operating Requirements**

	MINIMUM	MAXIMUM			
		60 Hz	50Hz		
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)			
Water Temp.	40°F (4.4°C)				
Water Pressure	20 PSIG (1.4 BAR)	120 PSIG (8.3 BAR)			
Remote Cond. Temps	-20°F (-29°C)	120°F (50°C)			

### **Dimensions**

ALL MODELS						
W x D x H (in.)	21 x 24 x 27					
W x D x H (mm)	533 x 610 x 686					

# **Specifications**

			duction 24hrs	gallons per 100	r Usage 5 lbs (45 kg) of Ice /70°F (21°C) water per 100 lbs					
Model Number	Cond. Unit		90°F (32°C) air/ 70°F (21°C) water lbs (kg)	Potable	Condenser	(45 kg) of ice @ 90°F (32°C) air/ 70°F (21°C) water	Voltage Characteristics	Min. Circuit Ampacity	Max Breaker Size	Approx. BTUs per hour**
GEM065 0A	Air	740 (336)	500 (227)		-	4.9		22.3		
GEM065 oW	Water	770 (349)	595 (269)		115	3.7	115/60/1 220-240/50/1	20.9	30	6,330 5,200
GEM065 oR	Remote*	770 (349)	505 (229)	12.0	-	5.4		22.5		
GEM0655A	Air	665 (302)	494 (224)		-	4.8		10.7		
GEMo655W	Water	699 (317)	578 (262)		87.5	3.7		10.1		

\*Requires RGA-1061-HM Remote Condenser with optional grill guard kit \*\*BTUH is calculated 0°F Evaporator, 110°F Condensing, and 33 PSIG. When installing a modular GEM on a drink dispenser, the **KGEMDISP MUST** be used.

NOTES:

Number of Wires: Approx. Shipping Weight lbs (kg):

3 (including ground)

GEM0650A 205 (93) • GEM0650W 220 (110) • GEM0650R 220 (100) • GEM0655A 205 (93) • GEM0655W 200 (91)

Refrigerant Type: GEM0655A = R404A • GEM0655A-49 = R449A